

### Standard Specifications

- Tyres (Non-Marking Solid) 406 x 127
- Drive (Nominal) 24V Electric 2.5kW
- Batteries 4x 6V 220A/hr
- Charger (120/240V -50/60Hz) 20 Amp Automatic
- Hydraulic System 15L

### Performance

- Working Height 11.75 m
- Platform Height - Elevated 9.75 m
  - A. Platform Height - Lowered 1.38 m
  - B. Platform Railing Height 1.10 m
  - C. Stowed Height (Rails Folded) 1.97 m
  - D. Platform Size Inside (W x L) 1.07 m x 2.16 m
  - E. Deck Extension 0.88 m
  - F. Overall Width 1.22 m
  - G. Overall Length 2.41 m
  - H. Wheelbase 1.85 m
  - I. Ground Clearance (centre of machine) 10 cm
- Platform Capacity <sup>1</sup> 320 kg
- Capacity on Deck Extension 120 kg
- Lift/Lower Time 60 / 60 sec.
- Maximum Drive Height 9.75 m
- Machine weight <sup>2</sup> 2,750 kg
- Maximum Ground Bearing Pressure 7.60 kg/cm<sup>2</sup>
- Drive Speed - Lowered 4.0 km/h
- Gradeability 25%
- Turning Radius - Inside 1.22 m
- Turning Radius - Outside 3.18 m

<sup>1</sup> Capacities shown are maximum with 2 persons indoors on both models.

Outdoor ratings are: 6RS - 1 Person/230kg ; 10RS - 1 person/320kg

<sup>2</sup> Certain options or country standards may increase weight and/or dimensions.



### Dimensions

